

Acifoam

Acidic foam cleaner-descaler

VF10



Diverclean[™]

Acifoam is an acidic based foam cleaner designed for daily and periodic application in the food, beverage and dairy industries.

Key properties

Acifoam is an acidic foam cleaner based on inorganic acid and a blend of high foaming wetting agents/emulsifiers. It is specially formulated for the removal of water hardness scale and other mineral deposits from food processing equipment and plant.

Acifoam is recommended for the periodic cleaning and descaling of high temperature processing equipment, such as cooking vessels, and also the exteriors of filler equipment, storage tanks, conveyors etc. It is also effective for daily application to break down protein deposits in the fishing industry.

Acifoam is suitable for use with a wide range of foam application equipment.

Benefits

- ▶ Effective scale remover
 - ▶ Foam application extends contact time with vertical surfaces
 - ▶ Suitable for use on aluminium
 - ▶ Free rinsing
-

Acifoam VF10 Use Overview

Directions for use

Use Acifoam at concentrations between 3-10% v/v depending on the type and degree of soiling. For specific details please refer to individual method cards.

Technical data*

Description	
Appearance	Clear, pale brown liquid
Relative Density at 25°C	1.28 - 1.30
pH (neat)	<1.5
Chemical Oxygen Demand (COD)	147 gO ₂ /kg
Nitrogen Content (N)	none
Phosphorous Content (P)	137 g/kg

* The above data is typical of normal production and should not be taken as a specification

Packaging

25 Kg

Safe Handling and Storage Information

Store in original closed containers or (where applicable) in an approved bulk tank, away from extremes of temperatures.

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

Product compatibility

Acifoam is suitable for use on materials commonly found in the processed food industry, including soft metals such as aluminium, when applied at the recommended concentration and temperature. Always rinse surfaces thoroughly after use (within 1 hour).

In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.



CORROSIVE

For More Information

Please contact your local Diversey representative.

Diversey India Pvt. Ltd.

501, 5th Floor, Akruti Centre Point, MIDC Central Road, Andheri (East), Mumbai 400 093. INDIA

Tel.: +91 22 6644 4222, Fax: +91 22 6644 4223

Toll Free No.: 1800 209 2095 • Website: www.diversey.com

Only for professional users / specialists. The manufacturer guarantees the quality of this product. Application recommendations are based on tests and practical experience; the manufacturer declines all responsibility for damages from improper product use.

Diversey
for a cleaner, healthier future™