

Dicolube SU 846Synthetic conveyor lubricant

VL11



Dicolube SU 846 is a soap free, disinfectant conveyor lubricant, which can be diluted with water of any hardness without causing precipitation problems.

Purpose & Use

Its disinfectant properties prevent the formation of slimes under the conveyors. This leads to an improved general hygiene level in the bottling hall and improves worker safety since the floors under the conveyors are less slippery.

The product exhibits excellent detergency, which will greatly reduce the time needed to clean the conveyors after production; thus saving labour time. Dicolube SU 846 can be used for glass, PET and cans. It has been approved by Coca Cola for use on returnable PET bottles. The low level of COD and nitrogen in this product reduce effluent charges compared to soap based lubricants.

Use Overview

Directions for use

Use concentration: 0.2 - 0.5%, depending on type and speed of conveyors.

Technical data*

Description			
Appearance	Clear, Yellow Liquid		
Specific gravity at 20°C	0.95 - 1.05 g/cm³		
pH (1% solution)	5.5 - 6.2		
Solubility	miscible in all proportions		
Viscosity at 25°C	20 - 30 mPa/S		

^{*} The above data is typical of normal production and should not be taken as a specification

Safe Handling and Storage Information

Wear gloves, apron and goggles or face shield. Severe eye irritant. When eye contact occurs, flush immediately and thoroughly with water and continue for at least 15 minutes. Obtain medical attention urgently.

_					•	
		~	V 3	\sim	ın	
	а	ч	ka	ч		ч
				_		

25 Kg, 200 Kg

Remark

Before the first use of Dicolube SU 846, all traces of soap based lubricants should be thoroughly removed since this lubricant is incompatible with soap based products, resulting in a loss of lubricity. *Dicolube SU 846 is not recommended where the Sulphate content in the infeed water is more than 40 ppm.*

Precautionary Statement

Full details on the handling and disposal of this product is given in a separate Material Safety Data Sheet.







DANGEROUS TO ENVIRONMENT

For More Information

Please contact your local Diversey representative.

Diversey India Pvt. Ltd.

501, 5th Floor, Ackruti Centre Point, MIDC Central Road, Andheri (East), Mumbai 400 093. INDIA Tel.: +91 22 6644 4222, Fax: +91 22 6644 4223

Toll Free No.: 1800 209 2095 • Website: www.diversey.com

Only for professional users / specialists. The manufacturer guarantees the quality of this product. Application recommendations are based on tests and practical experience; the manufacturer declines all responsibility for damages from improper product use.

