

# Super Dilac

## Heavy duty acidic CIP detergent descaler

**VA4**



**Diverflow**<sup>™</sup>

---

**Super Dilac is a low foaming, high active, non-fuming nitric / phosphoric acid detergent descaler for use in a wide range of CIP applications in the Food and Beverage industry.**

---

### **Key properties**

Super Dilac is highly effective at removing inorganic scale deposits, including calcium oxalate (beerstone). Super Dilac is low foaming and suitable for use in CIP applications under conditions of high pressure and turbulence.

Super Dilac is highly economical at in use concentrations.

Super Dilac is a conductive liquid detergent and suitable for automatic dosing and control.

---

### **Benefits**

- ▶ Highly effective in removing most inorganic scale deposits, improving operational efficiency.
  - ▶ Can be used for the passivation of new stainless steel CIP and Bottlewashing installations.
  - ▶ Suitable for automatic dosing and control by conductivity, ensuring consistent delivery of product.
-

# Super Dilac VA4 Use Overview

## Directions for use

Super Dilac is typically used for descaling at concentrations between 2.5 - 13% w/w (2 -1 0% v/v) at temperatures between 20 - 60°C.

Super Dilac is typically used for CIP applications at concentrations between 1.0 - 2.5% w/w (0.8 -2% v/v) for descaling, depending upon the application and level of scale.

**N.B.** The exact concentration, time and temperature when using Super Dilac will depend upon the application.

All detergents and disinfectants should be thoroughly rinsed after use to remove them from all food and beverage contact surfaces.

## Technical data\*

Description	
Appearance	Clear colourless liquid
pH (1% solution at 25°C)	< 1.5
Chemical Oxygen Demand (COD)	none
Nitrogen Content (N)	85 g/kg
Phosphorous Content (P)	21 g/kg

Super Dilac [% w/w]	Specific conductivity at 25°C [mS/cm]
0.5	12.8
1	25.1
2	46
3	66
4	85

\* The above data is typical of normal production and should not be taken as a specification

## Packaging

30 Kg

## Safe Handling and Storage Information

Store in original closed containers or (where applicable) in an approved bulk tank, away from extreme temperatures. Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

## Test method

Test method is available on request.

## Product compatibility

Super Dilac is safe for use on all type of materials commonly found in CIP circuits when applied under the recommended conditions. In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.



**CORROSIVE**

## For More Information

Please contact your local Diversey representative.

### Diversey India Pvt. Ltd.

501, 5th Floor, Ackruti Centre Point, MIDC Central Road, Andheri (East), Mumbai 400 093. INDIA

Tel.: +91 22 6644 4222, Fax: +91 22 6644 4223

Toll Free No.: 1800 209 2095 • Website: [www.diversey.com](http://www.diversey.com)

Only for professional users / specialists. The manufacturer guarantees the quality of this product. Application recommendations are based on tests and practical experience; the manufacturer declines all responsibility for damages from improper product use.

**Diversey**  
for a cleaner, healthier future™