

TASKI Nobile Plus

High gloss crystallizer



Taski Nobile Plus a product used for wet crystallization and protection of calcareous stone floors.

Features and Benefits

- > Quickly achieves a mirror-like shine thanks to a combined chemical and mechanical action
- ▶ Reduces water and dirt penetrability, thus facilitating daily cleaning and maintenance.
- Increases contour acuity and intensifies the natural appearance of the stone
- Significantly improves slip-resistance

TASKI Nobile Plus Use Overview

Dosages / Dilution:

Make the solution with 3 parts of powder and 1 part of water. Slowly add the water to the powder and shake the mixture to a homogeneous paste. Please ensure that the paste is shaken vigorously to ensure smooth dispersion. When the paste has to applied on the surface shake the mixture adequately so that the crystals don't settle down and are adequately spread over the floor.

Directions for use

- 1. If the floor has visible scratches, then hone the surface using 400 grit diamond pad for 2 mins per sgm and followed by 1800 or 2000 grit diamond pad for 5 mins per sqm before subjecting to the crystallisation.
- 2. Use 1% neutral cleaner solution and clean the surface using single disc machine with red pad and then vacuum it. Ensure proper rinsing with water to remove all dirt particles. Prepare paste by taking 3 parts of Nobile Plus and 1 part of water. Use 40 gm paste per m².
- 3. Damp the floor using wet mopping. Ensure it is just moist and no excess water on floor. Its extremely important to have the floor slightly moist before the application of Nobile Plus.
- 4. Spread the paste in the center of the application area. Place a 175 RPM single disc machine weighing a minimum of 110 pounds (50 kg), fitted with a red pad, directly on top of the paste.
- 5. Begin spreading the paste equally over the entire area to be treated.
- 5. Buff for 3-4 mins per m². Do not allow the paste to dry. Sprinkle a little water whenever required to maintain a creamy paste.
- 6. At the end of crystallisation, dilute the slurry with fresh water, pick it up with a wet vacuum cleaner. Flood and agitate the section thoroughly with plenty of neutral cleaner solution to ensure complete product rinse-off. Remove the solution with a wet vacuum cleaner.
- 7. After the floor dries completely, dry buff with a single disc machine, 200–1500 rpm, fitted with a soft white pad.

Technical data*

Description	
Appearance	yellow, solid powder
Bulk Density @ 20°C	1.05 gm - 1.15
pH-value (66%) solution	2.0 - 3.5

^{*} The above data is typical of normal production and should not be taken as a specification

Store in original closed containers, away from extremes

of temperatures. Full guidance on the handling and

disposal of this product is provided in a separate

Safe handling and storage information

Packaging 1 x 5 kg.

For scratched surfaces, grinding is recommended before the crystallization. Use only on calcareous stone floors, e.g. marble, travertine. Protect other surfaces from splashes. Use paste immediately after preparation. Keep container

Precautions

tightly closed.



HARMFUL



For More Information

Material Safety Data Sheet.

Please contact your local Diversey representative.

Diversey India Pvt. Ltd.

501, 5th Floor, Ackruti Centre Point, MIDC Central Road, Andheri (East), Mumbai 400 093. INDIA Tel.: +91 22 6644 4222, Fax: +91 22 6644 4223

Toll Free No.: 1800 209 2095 • Website: www.diversey.com

Only for professional users / specialists. The manufacturer quarantees the quality of this product. Application recommendations are based on tests and practical experience; the manufacturer declines all responsibility for damages from improper product use.

