SU727 (Oxofoam)

Chlorinated foam cleaner

Description

SU727 is a general purpose, chlorinated foam cleaner designed for daily use in the food, beverage and dairy industries

Key properties

SU727 contains a balanced blend of caustic alkali, surface active agents, sequestrant and hypochlorite. It is very effective for use on a wide range of food soils including animal and vegetable fats, blood and proteins. In addition, the presence of chlorine assists removal of organic and vegetable-based stains and helps to prevent build-up of "protein film" deposits.

SU727 is recommended for daily cleaning applications where heavy proteinaceous and fatty soiling are found in combination, such as abattoirs, poultry processors and the fish industry. It can be used for cleaning floors, walls, cutting tables, packing fillers, conveyors and other processing equipment.

SU727 is suitable for use with a wide range of foam application equipment.

Benefits

- · Effective for removal of heavy fat and protein
- Assists stain removal
- Helps prevent build-up of protein film
- Suitable for use in hard water
- Free rinsing

Use instructions

Use **SU727** at concentrations between 2-10% v/v depending on the type and degree of soiling. For specific details please refer to individual method cards.

Technical data

Appearance	: clear pale yellow liquid
Relative Density at 20°C	: 1.21
pH (1% solution at 20°C)	: 12.7
Chemical Oxygen Demand (COD)	: 89 gO ₂ /kg
Nitrogen Content (N)	: 1 g/kg
Phosphorous Content (P)	: 12 g/kg

The above data is typical of normal production and should not be taken as a Specification.

Safe handling and storage information

Store in original closed containers or (where applicable) in an approved bulk tank, away from sunlight and extreme temperatures. Keep away from acids. Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.



VF5





SU727 (Oxofoam)

Chlorinated foam cleaner

Product compatibility

SU727 when applied at the recommended concentration and temperature is suitable for use on the grades of stainless steel commonly found in the processed food industry. It is unsuitable for use on soft metals such as aluminium and galvanised materials. Always rinse surfaces thoroughly after use (within 1 hour). In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.

Test method

Test method is available on request.

For More Information

Please contact your local JohnsonDiversey representative.

JohnsonDiversey India Pvt. Ltd.

A-8, Laxmi Towers, Bandra-Kurla Complex, Mumbai 400 051. INDIA Tel.: +91 22 5644 4222, Fax: +91 22 5644 4223

The information contained in this document bulletin is to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. JohnsonDiversey disclaims any liability incurred in connection with the use of these data or suggestions.

