



Safoam

Mildly alkaline foam cleaner, soft metal safe, non-silicated

Description

Safoam is a mildly alkaline foam cleaner suitable for daily use in light-medium duty cleaning applications in the food, beverage and dairy industries.

Key properties

Safoam is based on a blend of mild alkalis, sequestrants and high foaming surfactants/wetting agents. Its balanced formulation provides an effective cleaning action without the need for harsh alkalinity or hazardous solvents. It is also suitable for use on most types of surfaces including plastics and soft metals, such as aluminium.

Safoam may be used for foam, manual or soak cleaning applications. Its mild alkaline formulation helps to penetrate and emulsify soil and is ideally suited for application in frozen foods operations, bakeries, canneries and snack food producers.

Safoam is suitable for use with a wide range of foam application equipment.

Benefits

- Mild but effective cleaner
- Use in soft and hard water
- Suitable for use on plastics and soft metals
- Free rinsing

Use instructions


Use **Safoam** at concentrations between 1-5% v/v depending on the type and degree of soiling. For specific details please refer to individual method cards.

Technical data

Appearance	: clear, colourless liquid
Relative Density at 20°C	: 1.07
pH (1% solution at 20°C)	: 10.6
Chemical Oxygen Demand (COD)	: 284 gO ₂ /kg
Nitrogen Content (N)	: 5.1 g/kg
Phosphorous Content (P)	: 8.5 g/kg

The above data is typical of normal production and should not be taken as a specification.

VF9



Diverclean™



Safoam

Mildly alkaline foam cleaner, soft metal safe, non-silicated

Safe handling and storage information

Store in original closed containers, away from extremes of temperatures. Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

Product compatibility

Safoam is suitable for use on materials commonly found in the processed food industry, including soft metals such as aluminium, when applied at the recommended concentration and temperature. Always rinse surfaces thoroughly after use (within 1 hour).

In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.

Test method

Test method is available on request.

For More Information

Please contact your local JohnsonDiversey representative.

JohnsonDiversey India Pvt. Ltd.

A-8, Laxmi Towers, Bandra-Kurla Complex, Mumbai 400 051. INDIA Tel.: +91 22 5644 4222, Fax: +91 22 5644 4223

The information contained in this document bulletin is to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. JohnsonDiversey disclaims any liability incurred in connection with the use of these data or suggestions.